



**Checklist**

- 1 x Blind
- Brackets - Amount varies depending width
- 2 Screws per Bracket
- 1 Pair of Hold Down Clips

**You will Require**

- Cordless Drill or Screwdriver, with Philips head bit

Brackets need to be mounted onto a firm surface, such as architrave or window frame. If mounting to other surface you will need to provide special plugs or anchors shown in this chart.

Plaster	Timber	Concrete, Stone, Brick or Tile
We recommend the use of The Ramset 10mm Grip Hollow Wall Anchor	Pre-drill holes and use the included screws.	Use a masonry drill and appropriate plugs, anchors or screws.

**Positioning Brackets**

Lay the blind at the window. The end brackets need to be mounted approximately 100mm's in from the ends. Make sure that the brackets will not interfere with the operation of the tilt mechanism inside the headbox, so keep this clear. Position extra brackets if required, spread evenly across the blind, not more than 900mm apart. When recessing the blind inside the frame, make sure the brackets are positioned in a straight line with each other.

**Mounting Blind**

Place the front hooks of the brackets to the inside front edge of the head rail. Rotate the headrail up into the rear of the bracket and lock into place.

**Large Blinds may require two people to support the blind to prevent damaging the headrail.**



**Hold Down Clips**


We recommend hold down clips are mounted to secure the base of the blind. They are designed to easily be removed from the bracket to enable you to lift the blind. Hold Down Clips are ideal for when the blind is mounted onto a door to prevent movement. When mounting the clips, do not place too much tension on the blind, allow for some slight movement. Place the pin into the end caps of the blind and lock in place into the bracket that are secure to the architrave or inside of window frame.

**Child Safety**

It is the responsibility of the person installing the blinds to make sure that child safety devices supplied by Blinds Online, ( for selected blind types) are installed. All warning tags are to remain on the blinds.

Due to the high risk of child/pet strangulation please ensure that cords are maintained and kept out of reach of danger

**⚠ WARNING**




Young children can strangle in the loop of pull cords, chain and bead cords, and cords that run through window coverings. They can also wrap cords around their necks. To avoid stangulation and entanglement, keep cords out of the reach of young children. Also,

1. install safety devices that remove the cord loop or reduce access to cords, and
2. move cots and furniture away from window covering cords.

**Cord Release Device WARNING:**

This cord release device reduces the strangulation hazard in the pull cord by removing the permanent loop. The cords should not be tied together and the cords should not be twisted around each other when the device is assembled. This device will not prevent strangulation if young children wrap pull cords around their necks. Always keep cords out of the reach of young children.

**⚠ WARNING**



Looped cords, looped bead chains or other flexible looped devices may cause a strangulation hazard for children under 5 years.  
**KEEP CORDS AND CHAINS OUT OF REACH OF CHILDREN**

If you have any further questions please contact our customer service team  
Ph: 1300 761 179 or email [Sales@blindsonline.com.au](mailto:Sales@blindsonline.com.au)