Child Safety Cord Tensioner

Important -If your Vertical blind has cord controls, it is essential that you fasten the child safety device onto your blind. This is a regulation in accordance with the child safety laws of Australia. Failure to secure this device may result in child or pet strangulation. We can not stress enough, how important this is. Blinds Online can not be held responsible if you omit fitting this device against our instructions.

Always make sure not to position beds or cots near a window.

Hook the clear polycarb cord tensioner onto the looped track cords. Screw into place,
making sure that there is a slight amount of slack on the cords
for it to be operated easily. The cords should not be too loose
that a child’s head could slip between the wall and the cords.

If mounting to the plaster for a face mount blind, make sure
that you screw into a stud. If unable to position on a stud you
will need to use a hollow wall anchor to secure in place.
Recess Mount
Face Mount

Handy Hints & Troubleshooting

• If you have multiple blinds, make sure to lay each one out at the individual windows before installing the first
one. This will ensure that you have the correct blinds at each window before positioning into place.

• For large blinds it helps to have a second person hold the track when attaching to the brackets. They can also
help hand the slats to you when hanging on the track, as these can often be heavy. This will also ensure that
you don’t drop and damage the track or slats.
• Chained slats sometimes have a little extra chain at the ends. This will need to be trimmed off once the slats
have been hung. Make sure to take your time and cut at the correct side of the slat (it is easy to make an error
and cut on the wrong side - even the professionals are known to do this from time to time).

• If the slats appear jammed when rotating for the first time, this will more than likely be because the slats have
been hung whilst the carriers were in the wrong position. Go back to Step 3, remove the slats and rehang whilst
the carriers are rotated square to the track (hook facing side, not forward or backward).

For further information please contact our customer service team Monday to Friday 9am to 5pm

Phone: 1300 761 179 or Email: sales@blindsonline.com.au

Hook the Pelmet bracket onto the rear lip of the track and lower into place

Choose. Measure. Order. Install. Easy.

Fitting the Optional Pelmet

Hook the brackets into the grooves of the pelmet as shown

space evenly along the pelmet

�Š