




Positioning the brackets




The position that you place the outermost brackets must be 5cm away from the end of the rail. Any additional brackets (supplied for wider blinds) can then be evenly distributed across the window space. Use a pencil to mark the window area where the brackets will be positioned.




Fitting the brackets

The brackets offer two methods of installation:



Top-Fixing


Use the single hole in the top of the bracket to fix to the lintel (the 'ceiling' of the recess).




Face-Fixing

Use two screws through the back plate to mount onto a facing surface (a wall or window frame)

Fitting the blind



Situate the front lip of the headrail into the front hook of the bracket.



Push the back of the headrail upwards to engage the metal clip at the back of the bracket.





3


Additional Information



If the blind appears too short when fitted, don't worry, it can take some time for the pleats to settle and loosen up when the blind is new. Leave the blind lowered for 24 hours and you should find that it begins to settle quite quickly. If you want to help it along, you can simply pull the blind down to its fullest extent and brush your hand vigorously down the pleats from top to bottom. **Do not attempt to adjust the cords.**



Cleaning the blind is easy; keep it free of dust using the brush attachment of a vacuum cleaner, and clean any marks or stains using a damp cloth or sponge. **Do not soak the blind fabric as this can cause the pleats to lose their shape.**



To remove the blind from the brackets, insert a flat head screwdriver into the tab protruding from the bottom of the rail, then gently pry it back while tilting the back of the rail downwards. Repeat this carefully for each bracket to release the rail.